

Aurora LT



The Aurora LT is a versatile and efficient dielectric earmuff with a 360° rotating headband. The adjustable three-position headband enables the usage with other safety equipment.

FEATURES

- Slim design
- Durable construction
- Head strap allows the use behind the head and under the chin
- Headband rotation of 360 degrees
- All-Plastic construction - Safe to use in high voltage environments
- Colors: Red

SNR 31 dB
NRR 24 dB

ATTENUATION VALUES	H = 35 db		M = 28 db		L = 20 db		SNR = 31 db		
Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Mean attenuation (dB)	13.2	15.0	26.8	32.9	35.0	39.3	36.6	36.0	34.9
Std. Deviation	2.5	1.5	3.8	3.2	4.6	1.6	4.8	4.5	4.2
APV-arvo (84%)	10.7	13.5	23.0	29.7	30.4	37.7	31.8	31.5	30.7

Bel II



The SILENTA Bel II is an extremely light-weight, all-plastic hearing protector with a 360 ° rotating headband. The all-plastic construction makes the Bel II di-electric and safe to use in high voltage environments and the rotating headband allows the user to combine it with other safety equipment. Its durability, versatility, wearing comfort and a prize-winning design makes the Bel II a true allrounder.

FEATURES

- Light and durable construction
- Slim line and ergonomic design
- Head strap allows the use behind the head and under the chin
- Headband rotation of 360 degrees
- All-Plastic construction – Safe to use in high voltage environments
- Weight only 114 g, 4.0 oz
- Color: Red
- Nato Stock Number 4240-58-000-0715

SNR 21 dB
NRR 20 dB

ATTENUATION VALUES	H = 25 db		M = 18 db		L = 12 db		SNR = 21 db		
Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Mean attenuation (dB)	9.4	10.5	22.0	21.7	29.5	35.2	35.8	33.4	32.1
Std. Deviation	3.2	2.2	2.3	2.6	4.5	3.2	3.4	4.4	5.1
APV-value (84%)	6.2	8.3	19.7	19.1	25.0	32.0	32.4	29.0	27.0

File download	Size
Brochure	1.28 MB